

TINT BASES FOR COLOUR EXPRESSIONS – SUPER EGGSHELL ENAMEL

TECHNICAL DATA SHEET NO.: A-88-F OCTOBER 2005

TINT BASE CODE:	TEE-range	THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS
Product Description	A range of tint bases to be used in the COLOUR EXPRESSIONS tinting system to produce a range of superior quality low gloss enamel paint colours for interior use.	
Characteristics	for a calculated volume of	re underfilled to levels which are specific for each tint base to allow f colourants to be added. The volume indicated on the container is dition of all prescribed colourants as per the formulation.
	recommended for use by the	colourants are unfinished or intermediate products which are not hemselves. A finished product is only produced once the prescribed we been intimately mixed with the tint base.
	<i>'</i>	product its technical features, product information, application and a comply with that of SUPER EGGSHELL ENAMEL (SEE 1), 85
Product Information	• TINT BASES :	Pastel Tint Base (TEE 1000) Deep Tint Base (TEE 2000) Transparent Tint Base (TEE 3000)
	Viscosity (Tint Bases) at 23°C S G at 23 °C (Tint Bases)	Approx. 78 KU (typical) 1,04 – 1,20 kg/ℓ (typical), varying over range.
	COLOURANTS to be used	The universal colourants specifically designed for use with the PLASCON COLOUR EXPRESSIONS tinting system.
Tinting Procedure	 Select the required colour and reference no. from the COLOUR EXPRESSIONS fandeck, other suitable fandecks or colour cards and locate the applicable formulation from the tables. Certain colour choices may require more than two coats to achieve full obliteration, (see 	
	 computer formulations for details in remarks column prior to tinting). Select the required tint base and volume for tinting and set the tinting machine to deliver the correct amount of colourants as per formulation. 	
Storage and Packaging	• Inject all required colourants, close container and shake on mechanical shaker for 5 minutes. Store away from direct sun, heat and severe cold. Packaging: Nominal 1 \(\ell \text{, 5 } \ell \) and 20 \(\ell \text{.}	

TECHNICAL DATA SHEET NO.: A-88-F

TINT BASES FOR SUPER EGGSHELL ENAMEL

Safety Precautions

- Always keep paint out of reach of children.
- Ensure good ventilation during application and drying.
- If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner. Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention. Harmful if swallowed. Seek medical attention and do not induce vomiting.
- Do not smoke while painting.
- Flammable. Store in a cool dry place away from heat and sparks.
- Refer to Material Safety Data Sheet for complete information.

Transportation

This product is non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996).

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B.: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

BARLOWORLD PLASCON SOUTH AFRICA (PTY) LIMITED

 CAPE TOWN:
 DURBAN:

 P O Box 42
 Private Bag X16

 Eppindust 7475
 Mobeni 4060

 Tel: (021) 534-6151
 Tel: (031) 451-3200

 Fax: (021) 534-3791
 Fax: (031) 451-3411

MOGALE CITY (KRUGERSDORP): Private Bag X4010 Kenmare 1745 Tel: (011) 951-4500 Fax: (011) 955-4136 PORT ELIZABETH:

P O Box 1594 Port Elizabeth 6000 Tel: (041) 401-1400 Fax: (041) 453-4596