



Barloworld
Plascon South Africa

PROFESSIONAL GALVANISED IRON PRIMER

TECHNICAL DATA SHEET NO.:
DATE:

L-41-F
OCTOBER 2004

PRODUCT CODE: PP 1000 THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product Description	A beige coloured waterbased primer for galvanised steel.		
Intended Uses	<ul style="list-style-type: none">For use over appropriately cleaned galvanised steel to provide good adhesion.		
Features	<ul style="list-style-type: none">A beige coloured waterbased primer which contains no lead, chromate, or other toxic ingredients.It may be overcoated with a wide range of topcoats such as alkyds, vinyl and waterbased types, two-pack polyurethanes, epoxies and nitro-cellulose not recommended.		
Product Information	Appearance	Semi-matt / low sheen	
	Colour	Beige	
	Solids	Approx. 52 % by mass; 39 % by volume	
	S G at 23°C	1,33 kg / ℓ (typical)	
	Recommended DFT	Min.: 25 µm	Max.: 40 µm
	Theoretical spreading rate	13 m ² /ℓ at 30 µm DFT	
	Typical spreading rate	Please apply appropriate correction factor	
	Viscosity at 23 °C	Approx. 93 KU	
	Flash point	> 65°C	
Application Details	Mixing	Stir thoroughly with a flat paddle until homogeneous.	
	Method	Brush, roller or airless spray.	
	Thinning	Water - see Application .	
	Cleaning	Water	
	Substrate	Well prepared galvanised steel.	
	Application Environment	Surface Temperature	Ambient Temperature
		Min.: 5 °C	Min.: 5 °C
		or 2 °C min. above dew point	
		Max.: 50 °C	Max.: 40 °C
		Max.: 85 %	
	Drying time	Touch dry	30 min at 23 °C
		Recoating -	
		with waterbased topcoat	2 h at 23 °C
		with solvent based topcoat	24 h at 23 °C
		Maximum overcoating	30 days
Storage and Packaging	Store away from direct sun, heat and severe cold.		
	Packaging: 5 ℓ and 20ℓ.		

PROFESSIONAL GALVANISED IRON PRIMER

Surface Preparation

- Ensure that surfaces are dry, sound, and free from dust, dirt, grease and oil before painting.
- 1. **GALVANISED STEEL:**
Remove all traces of temporary protective coating, dirt, grease, etc. from the surface using **GALVANISED IRON CLEANER (GIC 1)**. Remove all traces of the cleaner by rinsing with fresh water. Check surface for water break-free condition (i.e. water completely wets the surface without crawling back into droplets). If necessary, repeat the cleaning process until this condition is obtained. Allow surface to dry and apply the **PRIMER** the same day.
Prepare weathered surfaces as above to obtain a clean surface. Red and white rusted areas should be abraded back to bare metal and cleaned as above.
- 2. **PREVIOUSLY PAINTED SURFACES:**
Refer to **Technical Services Department**.

Application

- Apply by brush or roller. It can be sprayed using airless spraying equipment without thinning. However, if dilution is necessary, use a minimum amount of **WATER** only.

Cautions

- **NO NOT** thin with solvents - use only water.
- **DO NOT** mix with any other paint, including other galvanised iron primers.
- Do not overcoat with two-pack polyurethanes, epoxies and cellulose nitrate paints.
- Observe overcoating times.
- Avoid painting during inclement weather or if temperature is below 5 °C.

Safety Precautions

- Keep out of reach of children.
- Ensure good ventilation during application and drying.
- In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes – In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. If ingested give plenty of water / milk. Do not induce vomiting. Seek medical attention.
Refer to Material Safety Data Sheet for complete information.

Transportation

This product is non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996).

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B.: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

BARLOWORLD PLASCON SOUTH AFRICA (PTY) LIMITED

CAPE TOWN:

P O Box 42
Eppindust 7475
Tel: (021) 505-2400
Fax: (021) 534-3791

DURBAN:

Private Bag X16
Mobeni 4060
Tel: (031) 451-3200
Fax: (031) 451-3411

MOGALE CITY

(KRUGERSDORP):
Private Bag X4010
Kenmare 1745
Tel: (011) 951-4500
Fax: (011) 955-4136

PORT ELIZABETH:

P O Box 1594
Port Elizabeth 6000
Tel: (041) 401-1400
Fax: (041) 453-4596