



Barloworld
Plascon South Africa

WOODCARE WOOD PRESERVATIVE

TECHNICAL DATA SHEET NO.: S-8-L
DATE: OCTOBER 2005

PRODUCT CODE: FPR-range THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product Description	• A penetrating oil based coating for the protection and waterproofing of exterior timber.		
Intended Uses	• WOOD PRESERVATIVE protects, preserves and beautifies exterior woodwork, e.g. gables, window frames, laminated sections, weather boarding, split pole fencing, cladding and also prefabricated wooden building (domestic and industrial).		
Features	• WOOD PRESERVATIVE contains deep penetrating oils and waxes and an effective preservative for protection against fungal attack. WOOD PRESERVATIVE will not peel, crack or chip even after prolonged exposure.		
Product Information	Appearance	Suede	
	Colours	Clear	FPR 1
		Teak	FPR 19
		Mahogany	FPR 21
	Generic type	Oleoresinous with dry film preservatives	
	Solids	Approx. 40 % by mass; 30 % by volume	
	Practical spreading rate	Depends on substrate porosity up to 10 m ² /ℓ	
	Viscosity at 23 °C	12 - 14 " FC4 (typical)	
	S G at 23 °C	0,89 (typical)	
	Flash Point	38 °C	
Application Details	Mixing	Stir thoroughly with a flat paddle until homogeneous and occasionally during use.	
	Substrate	Well prepared wood surface.	
	Method	Brush or dipping.	
	Thinner	MINERAL TURPENTINE (AZH 1) - see Application.	
	Cleaning	MINERAL TURPENTINE (AZH 1) or POLYCELL BRUSH CLEANER PAINT AND GREASE REMOVER.	
	Application Environment	Surface Temperature	Ambient Temperature
		Min.: 5 °C	Min.: 5 °C
		Max.: 40 °C	Max.: 40 °C
	Drying time	Relative Humidity	
		-	
		or 2 °C min. above dew point	
Storage and Packaging	Packaging:	1 ℓ	5 ℓ
		Store away from direct sun, heat and severe cold.	
		Paint, UN1263, Packaging Group III, Flammable 3, Diamond detail	

WOODCARE WOOD PRESERVATIVE

Surface Preparation	<ul style="list-style-type: none"> All surfaces must be clean, dry and sound. Remove any oil, grease, mortar droppings, grime, dirt or any other contaminants. <ol style="list-style-type: none"> NEW WORK <ul style="list-style-type: none"> Sand wood to a smooth finish, working in the direction of the grain. Dust off. May also be applied to rough sawn timber, e.g. split pole fencing. This will, however, reduce the maintenance-free period. PREVIOUSLY VARNISHED OR PAINTED SURFACES <ul style="list-style-type: none"> It is essential to remove all previous varnish or paint completely with STRIPCLEAR SUPER PAINT STRIPPER (PR 17). Wash down with POLYCELL SUGAR SOAP POWDER CLEANER, rinse with clean water and allow to dry and sand smooth. Dust off. PREVIOUSLY COATED WITH WOOD DRESSING (FPR) <ul style="list-style-type: none"> Sand lightly to remove weathered material and restore surface to an even appearance. Dust off. STOPPING <ul style="list-style-type: none"> If required, use POLYCELL MENDALL 90 ALL PURPOSE ADHESIVE FILLER tinted with iron oxides to match the colour of the wood. Allow to dry for 24 hours and sand smooth.
----------------------------	--

Application	<ul style="list-style-type: none"> Ready for use by brush application. Application by brush ensures the best penetration into cracks, crevices, etc. If dipping is required, thin 4 parts WOOD PRESERVATIVE to 1 part MINERAL TURPENTINE (AZH 1) by volume. Normally two coats are sufficient. If, however, the substrate is extremely porous three applications may be necessary in order to produce an even finish. In that event the first coat will usually soak away immediately. Apply a further wet coat without delay to satisfy the absorbency of the substrate. Allow to dry. Then finish with a final coat. N.B. To prevent moisture penetration, the back and end grain of all timber to be used for house gables, hardwood door frames and window frames should be protected with two coats of WOOD PRESERVATIVE.
--------------------	--

Cautions	<ul style="list-style-type: none"> Do not use on toys and cots. Do not overcoat with paints and varnishes.
-----------------	--

Safety Precautions	<ul style="list-style-type: none"> Always keep paint out of reach of children. Ensure good ventilation during application and drying. If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner. Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention. Harmful if swallowed. Seek medical attention and do not induce vomiting. Do not smoke while painting. Flammable. Store in a cool dry place away from heat and sparks. Refer to Material Safety Data Sheet for complete information.
---------------------------	--

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B.: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

BARLOWORLD PLASCON SOUTH AFRICA (PTY) LIMITED

CAPE TOWN:

P O Box 42
Eppindust 7475
Tel: (021) 505-2400
Fax: (021) 534-3791

DURBAN:

Private Bag X16
Mobeni 4060
Tel: (031) 451-3200
Fax: (031) 451-3411

MOGALE CITY

(KRUGERSDORP):
Private Bag X4010
Kenmare 1745
Tel: (011) 951-4500
Fax: (011) 955-4136

PORT ELIZABETH:

P O Box 1594
Port Elizabeth 6000
Tel: (041) 401-1400
Fax: (041) 453-4596