



Barloworld
Plascon South Africa

WOODCARE WATERBASED WOOD VARNISH INTERIOR

TECHNICAL DATA SHEET NO.: L-114-A

DATE:

JULY 2004

PRODUCT CODE: IWW-range THIS SUPERSEDES ALL PREVIOUS PUBLICATIONS

Product Description	<ul style="list-style-type: none"> A premium quality, nano-particle water based wood varnish for interior use on wood.
Intended Uses	<ul style="list-style-type: none"> Ideal for use on most wooden surfaces such shelving, cupboards, skirting, panelling and General interior wood surfaces. For best results, surface preparation must be followed by a coat of PLASCON WOOD PRE-TREATMENT (WWP 1) before the application of a varnish

Features

- WATERBASED WOOD VARNISH INTERIOR is easy to apply, quick drying and non-hazardous.
- Environmentally friendly
- Low odour
- It's highly durable offering long lasting protection for all interior wooden surfaces.
- Excellent resistance to stains and repels water and moisture from penetrating the coating.
- Excellent adhesion to new and previously painted wood.

Product Information

Appearance and Colours	Semi- Gloss Clear, Mid brown and Oregon
Solids	Approx. 20 % by mass; 17 % by volume
Recommended DFT	Min.: 20 µm Max.30 µm
Theoretical Spreading Rate	7m ² /ℓ, depending on wood porosity and film thickness
Viscosity at 23 °C	75 - 85 KU (typical)
S G at 23°C	1,040 kg/ℓ (typical)
Flash Point	> 65 °C

Application Details

Mixing	Stir thoroughly with a flat paddle until homogeneous.		
Substrate	Well prepared wood surface.		
Method	Brush.		
Thinning	None – ready for use - see Application.		
Cleaning	Water		
Application Environment	Surface Temperature	Ambient Temperature	Relative Humidity
	Min.: 5 °C or 2 °C min. above dew point	Min.: 5 °C	-
	Max.: 40 °C	Max.: 40 °C	Max.: 85 %
Drying time	Touch dry	30 min at 23 °C	
	Recoating	4 h at 23 °C	
	Dry to handle	4 h at 23 °C	

N.B. Freshly painted windows, cupboard doors and drawers must be allowed to dry for at least 12 hours at 23 °C before closing.

Storage and Packaging

Store away from direct sun, heat and severe cold.
Packaging: 1 ℓ and 5 ℓ .

Transportation

This product is non-hazardous in accordance with Transportation and Classification of Dangerous Goods Act (1996).

WOODCARE WATERBASED WOOD VARNISH INTERIOR

Surface Preparation	<ul style="list-style-type: none"> All wood surfaces must be clean, firm and dry. For best results, surface preparation must be followed by a coat of PLASCON WOOD PRETREATMENT (WWP 1) before the application of a varnish <ol style="list-style-type: none"> NEW WOOD <ul style="list-style-type: none"> Sand in the direction of the grain, to a smooth finish with 150 grit paper. Remove dust with POLYCELL PAINT STRIPPER PREVIOUSLY VARNISHED WOOD IN GOOD CONDITION <ul style="list-style-type: none"> Sand to a Matt finish to create a bond/key between the old and new coat. Remove dust with POLYCELL PAINT STRIPPER PREVIOUSLY VARNISHED WOOD IN BAD CONDITION <ul style="list-style-type: none"> Remove old varnish by sanding or with POLYCELL PAINT STRIPPER. Sand bare wood to a smooth finish. Remove dust with POLYCELL PAINT STRIPPER WOOD PREVIOUSLY COATED WITH (WAX SEALER/OIL BASED WOOD PRESERVATIVE) <ul style="list-style-type: none"> Strip completely using POLYCELL PAINT STRIPPER. Deep sand to remove residual wax / oil from grain, sand until there is no evidence of any residual. Remove dust with POLYCELL PAINT STRIPPER PREVIOUSLY PAINTED WOOD <ul style="list-style-type: none"> Strip old paint by deep sanding or by using POLYCELL PAINT STRIPPER. Sand bare wood to a smooth finish. Remove dust with POLYCELL PAINT STRIPPER DISCOLOURED OR WEATHERED WOOD <ul style="list-style-type: none"> Sand with 100 grit paper to remove the discoloured or weathered layer. Sand bare wood to a smooth with 150 grit paper. Remove dust with POLYCELL PAINT STRIPPER KNOTS IN WOOD <ul style="list-style-type: none"> Apply Plascon WOODCARE KNOT SEAL (PK2) <p>NOTE: Do not thin Waterbased Varnish - apply as supplied. Freshly painted windows, cupboard doors and drawers must be allowed to dry for at least 12 hours at 23 °C before closing.</p>
Application	<ul style="list-style-type: none"> Do not apply in a dusty environment. Apply the first coat by brush. Allow to dry for 4 hours. Repeat second and third coats in the same manner Apply at least 3 coats to new and old wood. Sand lightly between coats with fine paper to denib. Dust off with wet cloth. This removes upstanding wood fibre ends and dust particles which could act as wicks to draw moisture in behind the film and shorten the life of the coating. Freshly painted windows, cupboard doors and drawers must be allowed to dry for at least 12 hours at 23 °C before closing
Safety Precautions	<ul style="list-style-type: none"> Always keep paint out of reach of children. Ensure good ventilation during application and drying. If accidental contact with skin should occur, wash immediately with soap and water or a recognised skin cleaner. Take care to avoid contact with the eyes. In case of contact, immediately rinse the eyes with plenty of water and seek medical attention. Harmful if swallowed. Seek medical attention and do not induce vomiting. Do not smoke while painting. Flammable. Store in a cool dry place away from heat and sparks. <p>Refer to Material Safety Data Sheet for complete information.</p>

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B.: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

NB: TO ORDER: Quote product name, product code number, packaging and colour.

BARLOWORLD PLASCON SOUTH AFRICA (PTY) LIMITED

CAPE TOWN:

P O Box 42

Eppindust 7475

Tel: (021) 505-2400

Fax: (021) 534-3791

DURBAN:

Private Bag X16

Mobeni 4060

Tel: (031) 451-3200

Fax: (031) 451-3411

MOGALE CITY

(KRUGERSDORP):

Private Bag X4010

Kenmare 1745

Tel: (011) 951-4500

Fax: (011) 955-4136

PORT ELIZABETH:

P O Box 1594

Port Elizabeth 6000

Tel: (041) 401-1400

Fax: (041) 453-4596

