

PROFESSIONAL HYGIENE LOW SHEEN

PRODUCT CODE: PHL 1 & THL 1000 Pastel Tint Base

TECHNICAL DATA SHEET

Product Description	Promotes a hygienic environment, offering good washability, durability and stain resistance.											
Intended Uses	Suitable for correctly primed interior new plaster, concrete, porous brickwork and various types of building boards.											
Features & Benefits	<ul style="list-style-type: none">• BIODEFENCE™ silver technology actively inhibits microbial growth between cleanings• BIODEFENCE promotes a more hygienic environment• BIODEFENCE helps reduce the risk of cross-contamination via painted surfaces• Low VOC < 16g/ℓ• Excellent washability and stain resistance• Low sheen• Ease of application and good hiding in 2 coats											
Product Information	Appearance	Low sheen										
	Colour	White (PHL 1)										
	Tint Bases	Pastel Tint Base ((THL 1000)										
	Solids	Approx. 53 % by mass; 40 % by volume										
	S G	1,33 (approx)										
	Calculated max. VOC	<16 g/ℓ for White and Pastel bases										
	Flash point	Non-flammable										
	Theoretical spreading rate	13 m²/ℓ @ 30 µm DFT per coat. This serves as a guide only										
	Practical spreading rate	The practical spreading rate will vary depending on the porosity and profile of the substrate, as well as the application technique and tools used.										
Application Details	Mixing	Stir thoroughly with a flat paddle until homogeneous.										
	Method	Brush, roller or airless spray.										
	Thinning	Ready for use, no thinning required										
	Cleaning	Water										
	Substrate	Thoroughly cleaned suitably primed concrete, plaster, brickwork, building boards and suitably primed wood, metal and fibre-board.										
	Application Environment	<table><tr><td>Surface Temperature</td><td>Ambient Temperature</td><td>Relative Humidity</td></tr><tr><td>Min: 10 °C</td><td>Min: 10 °C</td><td>Min: 10%</td></tr><tr><td>Max: 40 °C</td><td>Max: 40 °C</td><td>Max: 85%</td></tr></table>		Surface Temperature	Ambient Temperature	Relative Humidity	Min: 10 °C	Min: 10 °C	Min: 10%	Max: 40 °C	Max: 40 °C	Max: 85%
Surface Temperature	Ambient Temperature	Relative Humidity										
Min: 10 °C	Min: 10 °C	Min: 10%										
Max: 40 °C	Max: 40 °C	Max: 85%										
	Drying time	Touch dry 30 min @ 23 °C Dry to handle 1 h @ 23 °C Overcoating 1 h @ 23 °C										
Tint Bases	<ul style="list-style-type: none">• The tint base containers are underfilled to levels which are specific for each tint base to allow for a calculated volume of colourants to be added. The volume indicated on the container is only achieved after the addition of all prescribed colourants as per the formulation.• The tint bases and the colourants are unfinished or intermediate products which are not recommended for use by themselves. A finished product is only produced once the prescribed quantities of colourants have been thoroughly mixed with the tint base.• When mixed to a finished product its technical features, product information, application and surface preparation details comply with that of PROFESSIONAL HYGIENE LOW SHEEN (PHL 1). N.B. Only colourants from the Plascon Inspired colour system are permitted for use when tinting.											
Storage and Packaging	Store away from direct sun, heat and severe cold. Packaging: Nominal: 5 ℓ and 20 ℓ											

PROFESSIONAL HYGIENE LOW SHEEN

PRODUCT CODE: PHL 1 WHITE & THL 1000 Pastel Tint Base

Tinting Procedure	<ul style="list-style-type: none"> Select the required colour and reference no. from the INSPIRED COLOUR fandeck, other suitable fandecks or colour cards and locate the applicable formulation from the tables. Certain colour choices may require more than two coats to achieve full obliteration (see computer formulations for details in remarks column prior to tinting) Select the required volume for tinting and set the tinting machine to deliver the correct amount of colourants as per formulation. Inject all required colourants, close container and shake on mechanical shaker for 5 minutes. Note: UNDER NO CIRCUMSTANCES MUST COLOURS BE TINTED FROM PROFESSIONAL HYGIENE LOW SHEEN WHITE (PHL 1) - USE ONLY THE PRESCRIBED TINT BASE (THL 1000).
Surface Preparation	<p>Ensure that surfaces are dry, sound, and free from dust, dirt, grease and oil before painting.</p> <ol style="list-style-type: none"> NEW WORK <ol style="list-style-type: none"> Cement plaster, concrete and porous brickwork: Remove any loose particles and laitance by most suitable means and paint directly N.B. Soft underbound, friable and highly porous surfaces must be restored to a sound condition with PROFESSIONAL GYPSUM AND PLASTER PRIMER (PP 700). Gypsum plaster (e.g. Rhinolite, Creststone), brickwork stone work: Apply one coat of PROFESSIONAL GYPSUM AND PLASTER PRIMER (PP 700). If a gypsum plaster has been used as the joint skimming filler on gypsum board or dry wall partitioning, then seal these areas with PROFESSIONAL GYPSUM AND PLASTER PRIMER (PP 700). Fibre cement board: prime with BONDING LIQUID (CV1 14) or PROFESSIONAL GYPSUM AND PLASTER PRIMER (PP 700) Wood: Sand to a smooth finish and dust off. Seal knots and resinous areas with KNOT SEAL (PK 2). Prime with PROFESSIONAL WOOD PRIMER (PP 800) Mild Steel: Degrease with AQUASOLV DEGREASER (GR 1). Rinse thoroughly with water. Remove any rust by coarse sanding, mechanical grinding etc. or RUST REMOVER (RR 1). Prime general surfaces the same day with ZINC PHOSPHATE PRIMER (UC 170) or PLASCOSAFE (EMS 18) followed by PROFESSIONAL ALL PURPOSE UNDERCOAT (PU 800) Galvanised steel: Clean with GALVANISED IRON CLEANER (GIC 1) to achieve a water break-free surface. Rinse thoroughly with water. Prime the same day with PROFESSIONAL GALVANISED IRON PRIMER (PP 1000) PREVIOUSLY PAINTED SURFACES <ol style="list-style-type: none"> Previously painted surfaces in good condition: Remove loose and flaking paint back to a sound substrate and a firm edge by scraping and sanding. Spot prime bare areas with appropriate primer. Clean down with POLYCELL SUGAR SOAP POWDER CLEANER solution to remove all contaminants and chalked material. Rinse with clean water to remove all traces of sugar soap. Alternatively, clean with high pressure water jet. Sand glossy enamel surfaces to a matt finish and apply one coat of PROFESSIONAL ALL PURPOSE UNDERCOAT (PU 800). Previously painted surfaces in poor condition: Completely remove paint by most appropriate means e.g. scraping, coarse sanding or stripping with REMOVAL ALL PURPOSE COATINGS REMOVER (RRA 220). Ensure substrate is sound, not powdery or friable, prior to coating. Treat as for new work. FILLING Fill all imperfections with POLYCELL MENDALL 90 or the appropriate POLYFILLA and spot prime filled areas with PROFESSIONAL GYPSUM AND PLASTER PRIMER (PP 700). For wood use POLYCELL MENDALL 90.
Application	<ul style="list-style-type: none"> Apply two coats to new and suitably primed surfaces so as to achieve complete obliteration.
Caution	<ul style="list-style-type: none"> Do not apply to bare metal surfaces. Thinning affects the properties of the product Although PROFESSIONAL HYGIENE LOW SHEEN is anti-bacterial, normal cleaning and washing procedures must be adhered to.
Safety Precautions	<ul style="list-style-type: none"> Keep out of reach of children. Ensure good ventilation during application and drying. In case of skin contact, wash with soap and water or a recognised skin cleaner. Avoid contact with eyes. In case of contact, rinse eyes immediately with plenty of water and seek medical advice if symptoms persist. Harmful if swallowed. Do not induce vomiting. Seek medical attention. Refer to Material Safety Data Sheet for complete information.



PROFESSIONAL HYGIENE LOW SHEEN

PRODUCT CODE: PHL 1 WHITE & THL 1000 Pastel Tint Base

DISCLAIMER:

The recommendations contained herein are given in all good faith and are meant to guide the specifier or the user. They are based on results gained from our tests and experiences and are believed to be reliable. No guarantee is implied by the recommendations contained herein since conditions of use, method of application and cleanliness of the substrate prior to painting are beyond our control.

N.B. Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.

N.B. TO ORDER: Quote product name, product code number, packaging and colour.

KANSAI PLASCON (PTY) LIMITED

CAPE TOWN:

P O Box 42
Eppindust 7475
Tel: (021) 505-2400
Fax: (021) 534-3791

DURBAN:

Private Bag X16
Mobeni 4060
Tel: (031) 451-3200
Fax: (031) 451-3411

GAUTENG:

P.O. Box 4010
Luipaardsvlei 1743
Tel: (011) 951-4500
Fax: (011) 955-2841

PORT ELIZABETH:

P O Box 1594
Port Elizabeth 6000
Tel: (041) 401-1400
Fax: (041) 453 4606

PLASCON ADVISORY SERVICE: 0860 20 40 60

